


TRACKMOBILE® LLC

MOBILE RAILCAR MOVERS

HERCULES

FULL WIDTH CAB

Digital Instrumentation Display



Command Post Joystick



- Tier III Electronic Engine
- CAN-Bus Control System
- Larger Cab with controls integrated into seat
- Air Ride, High Back Swivel Seat with Joystick controls
- Automatic / Manual Power-Shift Transmission
- Digital Gauge Display
- On Board Diagnostics
- Neutral Braking
- Programmed Throttle Control
- 100 CFM Rotary Compressor

HERCULES



TRACKMOBILE® LLC

MOBILE RAILCAR MOVERS

1602 Executive Drive
LaGrange, Georgia 30240 USA
(706) 884-6651 Fax (706) 884-0390
www.trackmobile.com

MAXIMUM TRACTIVE EFFORT:

- 45,078 lbs [20,447 kg] to 46,332 [21,016 kg] double coupled
- 28,743 lbs [13,038 kg] to 29,997 lbs [13,606 kg] single coupled

DRIVE TRAIN CONFIGURATION:

- Power transmitted through torque converter, transmission, and transfer case to a No-Spin differential and planetary axle assemblies.
- **Engine:** Cummins QSB6.7 turbocharged diesel engine. 6 cylinder, 4 cycle, 160 HP [119KW] Tier III Max torque 539 ft. lbs [731 NM].
- **Transmission and Torque Converter:** Funk DF Series, four speed forward and reverse.
- **Transfer Case:** Heavy duty hardened alloy steel spur gears, Oil bath lubrication.
- **Rail Drive Axles:** Two Axletech Model PRLC, planetary type.
- **Roadwheel Drive:** Interlocking lug drive.

FRAME:

Heavy-duty, 2" [51 mm] thick welded frame.

BRAKES:

- **Rail & Road:** Hydraulic actuated disc brakes.
- **Train Brakes:** 100 CFM
- **Parking:** Spring applied, air released, disc/caliper arrangement.
- **Neutral Braking:** Automatically applies when brakes in neutral.

RAILWHEELS:

27" [686 mm] heat treated cast steel (AAR) specification.

ROADWHEELS:

16 ply 9.00x20 heavy duty mine service, rubber tires.

RAIL GAUGE:

Standard gauge: 56 1/2" [1435mm]

ELECTRICAL SYSTEM:

12 Volt DC, 160 Amp Alternator, 925 CCA Dual Batteries.

AIR INTAKE SYSTEM:

3 Stage Filtration, primary + safety element.

POWER STEERING:

Hydraulic steering system, pivoting steering wheel.

HYDRAULIC SYSTEM:

Constant pressure hydraulic system, with piston pump.

COUPLERS:

Two heavy-duty cast steel. AAR style, Air operated, electrically controlled knuckle release.

SANDERS:

Air operated, electrically controlled eight sanders.

LIGHTS:

Operator's cab, interior dome, one clear, one red.
 Rail Mode & Road Mode - 6 LED lights. 3 each front & rear.
 2 tail & stop combination, rear mounted.
 2 Lateral work lights to illuminate roadbed.

OPERATOR CAB:

Totally enclosed 360 degree visibility. Sound lever under 85 dBA. Two doors, in rear. Isolation mounts for body frame and cab. Operator air suspension seat with 180° swivel, Passenger seat with 180° swivel. Full instrumentation with digital video display. Cup holders, Rear coupler alignment camera, Arm rest controls, Rearview mirror, Cab heater, Defroster fans, Sun visor, Windshield wipers and washers, Strobe light, Fold down jump seat.

WARNING SIGNAL:

Blast type air horn, automatic backup alarm for road operation, Electric alarm.

Options:

5 & 10# fire extinguishers, air bell, air conditioning, auxiliary transmission oil cooler, performance package (additional 3,800 lbs and 185 HP), battery wrap heater, cab window extension, camera location options, cold weather fluids, cylinder rod protectors, engine block heater, engine oil pan heater, foam filled tires, (GCS) Ground Control System, hydraulic tank heater. MAX-TRAC wheel slip control, MAX-TRAN® automatic weight transfer system, radio control, switch control spot light, train air charge indicator, transmission oil heater, track mirrors/cab side, track mirrors/off side, turn signals, V shaped snow plow, wide traverse couplers for sharp curves/long cars.

HERCULES DIMENSIONS		
	On Rail AAR Clearance Pattern Maintenance	On Road
Wheel Base	127.0" 3226 mm	65.4" 1661 mm
Length	170.0" 4318 mm	170.0" 4318 mm
Width	101.0" 2565 mm	101.0" 2565 mm
Height	** 136.2" 3691 mm	144.6" 3673 mm
Weight	37,022 lbs. [16,828 kg]	

TABLE OF PERFORMANCE			
Maximum Speed* (Both Directions)	On Rail		On Road
Low	2.4 MPH	[3.9km/h]	1.5MPH [2.4 km/h]
2nd gear	4.0 MPH	[6.4 km/h]	2.5 MPH [4.0 km/h]
3rd gear	8.0 MPH	[12.9 km/h]	5.1 MPH [8.2 km/h]
4th gear	13.6 MPH	[21.9 km/h]	8.7 MPH [14.0 km/h]

*Actual speeds obtained will depend on grade, load, track conditions and other factors.

**Shipping height will increase by 1 1/2" due to rail flange plus any necessary truck blocking required.

Trackmobile® LLC reserves the right to change specifications at any time without prior notice.

TRACKMOBILE® LLC

1602 Executive Drive
 LaGrange, Georgia 30240 USA
 (706) 884-6651 fax (706) 884-0390
 E-Mail: trackmobile@trackmobile.com
 www.trackmobile.com

