

Rail Maintenance Equipment

SPIKE DRIVER

SEPTEMBER 2017

SPIKE DRIVER AMECO CX

Serial #	411008	411009	411010	411011	411012	411013
Engine Serial #	73391773	73392148	73192148	73392164	73392565	73393492
• Hours	1135	1140	1323	1371	1151	1102
• Operating Conditions	<ul style="list-style-type: none"> Missing hammer system. Right and left side disassembled Missing fire extinguishing system 	<ul style="list-style-type: none"> Batteries not charged 	<ul style="list-style-type: none"> Batteries not charged Missing fire extinguishing system 	<ul style="list-style-type: none"> Batteries not charged Missing hydraulic propulsion motor Missing fire extinguishing system 	<ul style="list-style-type: none"> Batteries not charged Missing fire extinguishing system 	<ul style="list-style-type: none"> Missing fire extinguishing system

* Shipped in Puerto Bolívar or truck in Cerrejón, Colombia

GENERAL SPECIFICATIONS

• Trademark	AMECO
• Model	CX
• Year	2012



GENERAL INFORMATION

• Function	<ul style="list-style-type: none"> Mechanically adjusts the spikes that secure the new rail to the ties.
• Travel Speed	<ul style="list-style-type: none"> 25 Mph (Maximum)
• Capacities	<ul style="list-style-type: none"> Fuel Tank: 120 gallons Hydraulic Tank: 110gallons
• Engine	<ul style="list-style-type: none"> JOHN DEERE 4045TF; 99 HP, four-cylinder, turbo diesel-fired (140HP engine required with auto spike feeder option)
• Brakes	<ul style="list-style-type: none"> Four-wheel shoe type, spring-actuated, hydraulic-release
• Hydraulic System	<ul style="list-style-type: none"> Pumps: Vickers PVH Series Control Valves: Vickers manifolded Oil Cooler: Electric fan, 80 GPM
• Electrical System	<ul style="list-style-type: none"> Battery: 24 vdc (dual 12V DC batteries), 1150 cold-cranking amps
• Axle Drive System	<ul style="list-style-type: none"> 3-inch standard (3 7/16-inch with bulk loader option)/ 16- inch diameter, cast steel

TECHNICAL SPECIFICATIONS

GENERAL

• Weight	28,750 Lbs (30,350 Lbs with Bulk Loader Option)
• Length	25' 8"
• Width	8' 6"
• Height	9' 10"
• Wheel Base	13' 6"
• Travel/Work Speeds	25 Mph (Maximum)