

ORDER NO	DATE
PAYMENT TERMS	

ASPEN EQUIPMENT COMPANY
1525 SE Cortina Dr
Ankeny IA 50021-3903
515-965-1000

CUSTOMER NO
CUSTOMER PO

**EQUIPMENT INVOICE
PROFORMA**

INVOICE TO:

SHIP TO:

SALES REP

DELIVERY TERMS

EQUIPMENT ORDER

UNIT	QTY	UNIT PRICE	TOTAL
------	-----	------------	-------

2024 Elliott L65R
Working Height- 65 feet
Side Reach- 56'-6" (Center of rotation to end of platform)
Platform Capacity- 600 lbs.
Rear Mount Turret with Boom Stowed Over the Truck Cab
Certified ANSI A92.2 for Vehicle-Mounted Elevating and Rotating Aerial Devices
Boom- 3-section 4-plate design
Lift Cylinder- 6" Double Acting
Boom Extension- Hydraulic (No Cables)
Continuous Rotation
Oil Reservoir- Steel, 30 gallon capacity includes Sight and Temperature Gauge. Located Back of Turret Box
Subframe-High Strength Full Length
Lower Controls- Electric over Hydraulic on Turret
Rear Outriggers- 17'-0" Out and Down Outriggers
Secondary Outriggers- 12'-0" Out and Down Outriggers
Outrigger Controls- Rear of Bed Each Corner. Electric Over Hydraulic
Cable Carrier- Full Length with Tube for Hoses and Cables. Includes Cover
Platform- Hydraulic Self Leveling with 160 Degrees of Rotation. Aluminum Floor.
Hydraulic Pump- Fixed Gear
USB outlet at upper controls
PTO Hour Meter
Chassis Control- Start/Stop, Throttle and Horn Located at Rear Bumper, Lower Turret Controls and Upper Platform
Automatic Rotation Lockout - Prevents Boom from Rotating to Side Where Outriggers Are Not Fully Extended Horizontally
Emergency Pump- 12-volt with Switch at Lower Turret and Upper Platform
Backup Alarm
LED Lights- Bed marker, Stop / Tail / Turn, and Reverse
Safety Kit- Fire Extinguisher, Safety Triangle Kit, and Two Body Harnesses with Lanyards
Manuals- (1) Operation, Maintenance and Safety, (1) Parts and (2) Electronic copies of each
Maintenance Filters- (1) extra high-pressure and (1) return filter

Options equipped
40" x 60" (standard)
110 Volt Line to Platform
Sign Forks - (2) Extendable
UPPER CONTROLS - 4 Single-axis joysticks - hardwired
PLATFORM ACCESS -Walkway with steps and handrails. Includes boom rest
LIFTING -5,900 lb. Planetary Winch With Anti-Two-Block Switch, Two Part Hook, Cable Packer, 180' of 3/8" Cable, 2-part block & Retainer Lug
500 lb. Platform Mounted Jib With Hydraulic Winch. Jib Stows in Platform.
Hot Shift PTO For Automatic Transmission
Steel- 14'-6" (For use with a cross box) Includes stake pockets and tie down rail. Black Grip Deck
BUMPER OPTIONS - Angle (3-steps with grab handles)
TOOL BOX OPTIONS - 98" x 36" x 24" Aluminum Crossbody Box
CONVENIENCE BUNDLE - One button operation- "Extended Platform Stow"- Automatically stow the platform from various positions within the platform and lower controls, "Platform Unstow"- Unstow the platform to either side of the chassis at lower controls, "Chassis Auto-Level"- Automatically level the chassis with outriggers, "Outrigger Stow"- stow outriggers automatically.



ORDER NO	DATE
PAYMENT TERMS	

ASPEN EQUIPMENT COMPANY
 1525 SE Cortina Dr
 Ankeny IA 50021-3903
 515-965-1000

CUSTOMER NO
CUSTOMER PO

**EQUIPMENT INVOICE
 PROFORMA**

Arctic Fox Reservoir Heater Tied to Truck Cooling System (5,000 BTU)
 Mounting Bracket Above 8' Crossbody Box for Customer Installed Welder/Generator (Designed for Miller Bobcat 225)
 Remote Start/Kill Switch in Platform for Customer Installed Welder/Generator
 Welder Leads to Platform - (2) 1 Gauge Cables
 HiReach Unit Painted Red, Subframe Painted Black, Outriggers Painted Red
 CHASSIS - 2024 Freightliner M2 106, 280 hp Cummins B6.7 diesel engine (660 lb/ft), 198" WB, 132" C.A., 90" AF, Allison 2500 RDS automatic transmission, 29,000 GVWR, 10,000 lb front axle, 19,000 lb rear axle, 11R22.5 front and rear tires, hydraulic brakes, 50 gallon alum fuel tank (LH), AM/FM radio, cruise control, power windows, power locks, tilt steering, air conditioning, air ride driver seat, two-man pass. bench seat. Color: White. 1-year tow warranty